## Claims

- [c1] An oil separator for an internal combustion engine, comprising:

  a basket sealingly mounted to a valve cover of an engine, the basket containing at least one vent for allowing blow-by gas and oil particles to pass therethrough; a breather lid sealingly mounted to the basket; and a filter media disposed between the basket and the breather lid for separating oil particles from the blow-by gas.
- [c2] The oil separator according to Claim 1, wherein the basket forms a seal with the valve cover.
- [c3] The oil separator according to Claim 1, wherein the basket forms a seal with the breather lid.
- [04] The oil separator according to Claim 1, wherein the breather lid includes an outlet port for allowing the blow-by gas to exit the oil separator.
- [05] An oil separator for an internal combustion engine, comprising:
  a basket sealingly mounted to a valve cover of an engine, the basket containing at least one vent for allowing

blow-by gas and oil particles to pass therethrough; a breather lid sealingly mounted to the basket; and means disposed between the basket and the breather lid for separating oil particles from the blow-by gas.

- [c6] The oil separator according to Claim 5, wherein the basket forms a seal with the valve cover.
- [c7] The oil separator according to Claim 5, wherein the basket forms a seal with the breather lid.
- [08] The oil separator according to Claim 5, wherein the breather lid includes an outlet port for allowing the blow-by gas to exit the oil separator.